

XTL™ Labels

Heat-Shrink Tube (Continuous)

- DYMO XTL™ label makers print directly on continuous Heat-Shrink Tubes
- Heat-Shrink Tubes provide insulation when shrunk down and ensure a secure fit on wires and cables with a 3:1 shrink ratio
- Constructed of flame-retardant polyolefin sleeves and tested to industry standards
- Meets MIL-M-81531, MIL-STD-202G, SAE-DTL-23053/5 (Class 1 & 3)
- Easy-to-peel split back design makes applying labels quick and easy
- Durable thermal transfer printing technology – label text won't smear or fade
- RoHS compliant



Quick Specs

Label Widths	6, 12, 24, 54 mm
Tape Platform	XTL
Printer Compatibility	XTL 300: Up to 24 mm wide XTL 500: Up to 54 mm wide
Label Length	2.7 m (6, 12, 24 mm width) 1.8 m (54 mm width)
Printing System	Thermal Transfer
Temperature Rating	Max 125°C
UL Recognized	Yes, component to UL 224
Country of Origin	Belgium
Material	Heat Shrink

Item Number	Width	Color		Length (mm)	Width (mm)	Height (mm)	Weight (kg)	QTY	EAN
1868809	6 mm	A	Unit	72	35	120	0.05	1	071701001887
			Shelf	215	76	126	0.33	6	30071701001888
			Case	400	230	145	1.95	30	50071701001882
			Pallet	1200	800	1165	147.85	63	-
1868810	12 mm	A	Unit	72	35	120	0.06	1	071701001894
			Shelf	215	76	126	0.39	6	30071701001895
			Case	400	230	145	2.23	30	50071701001899
			Pallet	1200	800	1165	165.80	63	-

XTL™ Labels



Item Number	Width	Color		Length (mm)	Width (mm)	Height (mm)	Weight (kg)	QTY	EAN
1868811	24 mm	A	Unit	72	35	120	0.08	1	071701001900
			Shelf	215	76	126	0.55	6	30071701001901
			Case	400	230	145	3.06	30	50071701001905
			Pallet	1200	800	1165	217.78	63	-
1868812	54 mm	A	Unit	72	65	120	0.14	1	071701001917
			Shelf	215	76	126	0.47	3	30071701001918
			Case	400	230	145	2.67	15	50071701001912
			Pallet	1200	800	1165	193.21	63	-



A *NewellRubbermaid* Brand

This information is being provided for general information purposes and the compliance standards and certifications referenced herein are based on current standards which are subject to change.