

STEINEL HG 2420 E Hot Air Tool

Reliability for all demands: Electronically controlled HG 2420 E hot air tool. 2200 W, infinitely variable temperature setting from 80—650°C in 9 steps by thumb-wheel. Airflow regulation in 2 stages from 150l/min to 400l/min. suitable for construction site use, integrated fine dust filter. Outlet nozzle suitable for screw on professional nozzles.

For Professional users: The HG 2420 E electronically controlled hot air tool is a powerful performer on any construction. Greater protection from dust and moisture tougher design as well as a better insulated power chord to H07.

Features: 2200-watt brushless motor, rated for 1,000 hours of operation. The integrated fine dust filter protects internal component in dusty environments. The outlet nozzle is suitable for screw on professional nozzles.

Service Friendly: The power chord can be changed without opening the enclosure.

Accessories: A comprehensive range of Steinel nozzles and consumables. Also suitable for leister nozzles.

STEINEL HG 2420 E Hot Air Tool



STEINEL HG 2420 E Hot Air Tool

Technical Specifications electronically controlled hot air gun HG 2420 E

| | |
|-------------------------------------------|----------------------------------------|
| European article number (EAN) | 4007841008284 |
| Nominal Power Consumption | 2200 W |
| Temperature | 80—650°C |
| With Temperature control | Yes |
| With Temperature indication | Yes |
| Air Volume | 400L/min |
| Air flow Control | Positions |
| Weight of Machine | 0.610kg |
| Dimensions (LxWxH) | 357 x 75 x 89 mm |
| Voltage | 220—230V, 50/60 Hz |
| Min. Frequency | 50 Hz |
| Max. Frequency | 60 Hz |
| Power Consumption | 2200 W |
| Min. Temperature Range | 80°C |
| Max. Temperature Range | 650°C |
| Temperature Regulation | Yes |
| Min. Airflow Rate | 150L/min |
| Max. Airflow Rate | 400L/min |
| Airflow Regulation | 2 Stages |
| Motor | Brush Motor |
| Heating Elements | Ceramic |
| Protection Class (without earth terminal) | 2 |
| Thermostat | No |
| Thermal Cut-Out | Yes |
| Power Cord Length | 3 Metres |
| Weight | 0.610kg |
| Accessories | Using Steinel Professional Accessories |
| Special Features | 10mm Round Nozzle, Including Case |

