



## CFHR – HIGH SHRINK RATION CROSSLINKED POLYOLEFIN

High shrink ratio heat shrink tubing accommodates extreme differences between cables, connectors and backshells

### FEATURES AND BENEFITS

- Flame retardant
- Accommodates a wide variety of connector shapes and configurations
- Optional thermoplastic adhesive liner for complete environmental protection and insulation
- Shrink ratio: 6:1
- Continuous operating temperature: -55°C to 110°C
- Shrink temperature: 120°C min.

### STANDARDS

- UL-94-V-0 - UL file # E132914
- IEC 60684-3-247

### TYPICAL APPLICATIONS

- Wire harnesses
- Abrasion and impact resistance
- Strain relief and protection of cables and connectors



# 6:1

SHRINK RATIO

# -55°C to 110°C

# (-67°F to 230°F)

CONTINUOUS OPERATING TEMPERATURE

### MARKETS:

Electrical Utility, Industrial, Commercial, Mass Transit

### STANDARDS:



DSG-CANUSA PRODUCTS

Version: 04 2021/APR/21

Hilltop Products ltd - Web: [www.hilltop-products.co.uk](http://www.hilltop-products.co.uk) - Tel: 01942 723101 - Email: [sales@hilltop-products.co.uk](mailto:sales@hilltop-products.co.uk)

 SHAWCOR

# High shrink ratio crosslinked polyolefin

## DIMENSIONS

ORDER NUMBER	EXPANDED		RECOVERED				DELIVERY UNITS
	Internal Diameter (min) D		Internal Diameter (max) d		Total Wall Thickness (nom) W		Lengths
	MM	IN	MM	IN	MM	IN	1.22 M / 48 IN
0750	19.0	0.750	3.2	0.125	3.2	0.123	35
1300	33.0	1.300	5.5	0.220	3.4	0.135	60
1750	44.4	1.750	7.4	0.290	3.6	0.140	40
2000	50.8	2.000	8.3	0.330	4.3	0.170	25
2750	69.8	2.750	11.7	0.460	4.8	0.190	15
3500	88.9	3.500	17.1	0.673	4.3	0.170	10
4700	119.4	4.700	22.9	0.900	4.8	0.190	5



## ORDERING

Select a dimension which will shrink snugly over the application to be covered. If recovery is restricted the resultant wall thickness will be less than specified.

- Select options:
  - Printing: Printed or unprinted
  - Adhesive Lining: Lined (D) or unlined (U)
  - Lengths: 1.22 m or 7.62 m spool (unlined only)
- Please specify the product name, order number and options you require
- *Example:* CFHR, 0750, U, black, unprinted, 1.22 m length

Please contact your Customer Service Representative for information on custom colors, sizes, lengths and material data sheet.