

DERAY®-I – THIN WALL CROSSLINKED POLYOLEFIN

Universal heat shrink tubing with excellent physical and mechanical properties

FEATURES AND BENEFITS


- Self-extinguishing (colors only)
- Flexible
- Very good resistant to common fluids and solvents
- Excellent physical and electrical performance
- Shrink ratio: 2:1
- Continuous operating temperature: -55°C to 135°C
- Shrink temperature: 90°C min.

STANDARDS

- UL 224 125C ATF - UL file # E107857 (colors only)
- CSA 22.2 No 198.1 125C - CSA file # 066150_0_000 (colors only)
- DEF STAN 59-97 Type 2b
- BS G198 Part 3 Type 11B
- VG95343 Part 5 Type A/B
- QPL SAE AS23053/5 Class 1 + 2
- CNES approved and listed in Matrex database
- ECSS-Q-ST-70-02
- Approved to major automotive OEM specifications

TYPICAL APPLICATIONS

- Electrical insulation of wire splices and terminals
- Protection against chemical strength
- Strain relief of wire terminations
- Cable marking and bundling of electrical or mechanical components
- Secures components from abrasion and fluids



2:1
SHRINK RATIO

-55°C to 135°C
(-67°F to 275°F)
CONTINUOUS OPERATING
TEMPERATURE

MARKETS:

Automotive, Aerospace, Defense, Industrial, Mass transit

STANDARDS:



DSG-CANUSA PRODUCTS

Version: 04 2021/APR/21

 **SHAWCOR**

Hilltop Products Ltd - Web: www.hilltop-products.co.uk - Tel: 01942 723101 - Email: sales@hilltop-products.co.uk

Thin wall crosslinked polyolefin

DIMENSIONS

ORDER NUMBER	EXPANDED		RECOVERED				DELIVERY UNITS				
	Internal Diameter (min) D		Internal Diameter (max) d		Total Wall Thickness (nom) W		Spool*		Mini-Spool		Lengths
	MM	IN	MM	IN	MM	IN	M	FT	M	FT	1.22 M / 48 IN
0031	0.8	1/32	0.4	0.016	0.4	0.016	300	984	-	-	-
0047	1.2	3/64	0.6	0.024	0.40	0.016	300	984	150	492	25
0063	1.6	1/16	0.8	0.031	0.40	0.016	300	984	150	492	25
0094	2.4	3/32	1.2	0.047	0.50	0.020	300	984	150	492	25
0125	3.2	1/8	1.6	0.063	0.50	0.020	300	984	150	492	25
0187	4.8	3/16	2.4	0.094	0.50	0.020	300	984	75	246	25
0250	6.4	1/4	3.2	0.126	0.60	0.024	300	984	75	246	10
0375	9.5	3/8	4.8	0.189	0.60	0.024	150	492	75	246	10
0500	12.7	1/2	6.4	0.252	0.60	0.024	100	328	50	164	10
0625	16.0	5/8	8.0	0.315	0.60	0.024	100	328	50	164	10
0750	19.0	3/4	9.5	0.374	0.80	0.031	50	164	30	98	10
1000	25.4	1	12.7	0.500	0.90	0.035	50	164	30	98	10
1250	31.8	1 1/4	15.9	0.626	0.90	0.035	50	164	30	98	-
1500	38.0	1 1/2	19.0	0.748	1.00	0.039	50	164	30	98	-
2000	51.0	2	25.4	1.000	1.10	0.043	50	164	30	98	-
3000	76.0	3	38.0	1.496	1.30	0.051	25	82	15	49	-
4000	101.6	4	50.8	2.000	1.40	0.055	25	82	15	49	-

Clear items not UL or CSA listed.

*Delivery unit *spool* only available for black items



DSG-CANUSA PRODUCTS

We advise that customers should separately evaluate the suitability of our products for their particular application. Our responsibilities are only those listed in our Standard Terms and Conditions of Sale for these products. Please ask for the latest version of this data sheet. Subject to modification without prior notice.



Hilltop Products Ltd - Web: www.hilltop-products.co.uk - Tel: 01942 723101 - Email: sales@hilltop-products.co.uk